



PT 8303 Vented dryer

MIELE PROFESSIONAL. IMMER BESSER.

Efficient processes and perfect results. Miele's proverbial quality stands for fast and smooth processes. With their high-quality, low-maintenance design, our laundry machines are the reliable workhorses in a commercial working environment. In Miele's unique honeycomb drum, even the most delicate of fabrics are given the gentlest of treatment.

Economic use of resources and improved economics. With low costs throughout a machine's entire life cycle (total cost of ownership), our long-lasting laundry machines are an investment from which you will reap ample rewards - and thanks to numerous innovations will help save valuable resources.



PT 8303 Dryer at a glance:

- 35 lbs load capacity
- Load capacity supports commercial applications
- Stainless Steel H-axis Honeycomb™ drum with left hinged door
- Electric variant
- Residual moisture sensors for optimum throughput and results
- Alternating tumbling action for improved garment dispersion and ensures even and gentle drying that is crease-free
- The slim design, just 28" wide, fits in the smallest of spaces
- 180° door opening for easy loading and unloading
- Profitronic M control, freely programmable with preset programs for common washing applications

Highlights

- The slim design, just 28" wide, fits in the smallest of spaces
- Residual moisture controls for 12 programs

Trust the experts.

Miele Professional leads the way in developing innovative technology that meets the highest demands in washing, dishwashing, cleaning and disinfection in industrial and residential applications. Providing outstanding speed, capacity, and performance, Miele is the definitive source for precision cleaning equipment.

PT 8303 Vented dryer

Miele Professional. Immer Besser.

Machine	PT 8303
Machine exterior	Iron-Grey
Load capacity	35 lbs (15 kg)
Heating options	Electric
Width	28" (711 mm)
Min. width of delivery access to installation site	28 ⁹ / ₁₆ " (725 mm)
Height	70 ⁷ / ₈ " (1,800 mm)
Depth	42 ⁷ / ₈ " (1,089 mm)
Door opening Ø	20 ¹ / ₂ " (520 mm)
Drum volume	10.6 ft ³ (300 l)
Noise level in extraction	70 dBA
Exhaust duct Ø	6.3" (160 mm)
Max outlet airflow	483 ft ³ /min (821 m ³ /hr)
Weight	307 lbs (139 kg)
Electrical connection (standard)	3 AC 220-240 V 60 Hz
Electrical connection (convertible)	3 AC 208 V 60 Hz
Electrical connection (convertible)	2 AC 208 V 60 Hz
Material No.	11772780
Article No.	52830366USA

